



AATAC AHD SERIES CARRIER

Standard Equipment

- | | | |
|--|--|---|
| <ul style="list-style-type: none"> ● 20' - 26' steel body ● Dual front lift cylinders ● Extension cylinder with wear rings ● Tubular cab protector ● 96" wide body ● Dual illuminated control panels ● Stake pocket sides ● Positive lockdown system | <ul style="list-style-type: none"> ● 48"x18"x18" tool box with key ● Tow light socket ● Chassis reinforcing subframe ● 3/4 length lift frame ● Full length nylatron slide pads ● 50' cable ● Four rear tie down slots ● Variable speed hydraulic winch | <ul style="list-style-type: none"> ● Mud flaps ● PTO/Pump combination ● Complete installation hardware ● Sealed wiring connectors ● Factory pre-installed and tested |
|--|--|---|

Options

- | | | |
|--|---|--|
| <ul style="list-style-type: none"> ● Cable tensioner ● Winch remote free spool ● Extra tool boxes ● Stainless tool box door covers ● Independent wheel lift ● Removable side rails | <ul style="list-style-type: none"> ● Various cab protectors ● Snatch block ● Light bar ● Deluxe switch panel ● Work lights ● Hook up lights | <ul style="list-style-type: none"> ● D-rings ● Tool box lights ● Pintle hitch ● Trailer hitch ● V-chains and straps |
|--|---|--|

Specifications

Specifications	
	Steel
Load capacity	25,000
Platform size	20' - 26' x 8'
Floor	3/16" Solid smooth plate
Crossmembers	3"x4.1 58,000 PSI
Cable	50' 3/8" 6x37
Winch	10,000 extended

Chassis recommended 14,250 to 24,000 GVW. For ordering information call 1-800-228-0295