



AATAC ALUMINUM SERIES

Standard Equipment

- 92" Wide Aluminum Modular Body
- Enclosed Dual Illuminated Control Panels
- Dual Variable Speed Hydraulic Winches
- Tailboard Scotch Block Slots
- Rear D-Rings
- Mud Flaps
- Aluminum Aerodynamic Light Pylon
- Tunnel Tool Box
- Patented Dual-Trac Lift System
- Lift Arms and Storage Brackets
- Safety Chains with Storage Boxes
- Bolt-On Boom Tip
- Rustproof, Waterproof Taillights
- Sealed Wiring Connectors
- Tow Light Socket
- Federal Standard 108 Lighting
- Complete Installation Hardware
- Factory Pre-Assembled and Tested

Options

- Tow Sling
- Scotch Blocks
- Snatch Block(s)
- Push Bumper
- Bolt-On Boom Jib
- Trailer Hitch
- Standard and Self-Load Dollies
- Dolly Storage Tray
- Light Bar
- Deluxe Switch Panel
- Work Lights
- Hook Up Lights
- Deluxe LED Taillight Package
- Tool Box Lights
- Pintle Hitch
- Polished Aluminum Tailboard
- Frame Forks w/ Receivers
- Many More Popular Options!

SPECIFICATIONS FOR 10 TON ALUMINUM TOW TRUCK

Boom Specifications

Power rating	Retracted	20,000 lbs.
	Extended	7,000 lbs.
Boom height (Maximum elevation)	Retracted 11' 6"	
	Extended 16' 2"	

Wheel Lift Specifications

Capacity (with forks)	6,500 lbs. Retracted
	5,000 lbs. Extended
Capacity (with lift arms)	4,500 lbs. Retracted
	4,500 lbs. Extended

Winch

Rating (first layer)	10,000 lbs.
Cable	3/8" x 100'
Type	6 x 37 IPS Hemp Center
Safe work limit	3,5000 lbs. each

Truck Recommended

Cab to axle	84"
GVWR	11,000 - 20,000