

12-TON TOWING & RECOVERY UNIT



AATAC MEDIUM DUTY

Standard Equipment

- Dual Variable Speed Hydraulic Winches
- Power Boom Elevation
- Power Boom Extension
- Dual Illuminated Control **Panels**
- Tailboard Chain Slots
- Aerodynamic Light Pylon

Recovery Unit Boom Ratings:

Maximum Boom

Elevation:

- Rear D-rings
- 26 Cubic Ft. Tunnel Box
- Fiberglass Fender Flares
- Galvanized Inner Fenders
- Patented Dual-Trac Lift System
- Power Up & Down Underreach
- Power In & Out Underreach
- Power Dual Tilt System
- Retracted.....24,000 lbs Extended 7.000 lbs

Retracted......11'10" Extended......16'6"

Winches 10,000 lbs Each First Layer

Medium Duty Underlift

Retracted: with Forks......10.500 lbs with HD Lift Arms.....6,500 lbs Extended: with Forks......8,500 lbs with HD Lift Arms.....6,500 lbs

Chassis recommended 17,500 to 26,000 GVW, 84" or 108" CA Ratings are based on structural factors only, not vehicle capability. Product specifications are subject to change without notice.

- HD Lift Arms & Receivers
- Safety Straps and Rachets
- Frame Forks, Risers & Adapters
- Mud Flaps
- Bolt on Boom End
- Complete Installation Hardware
- · Pre-Assembled and Factory Tested
- Federal Standard 108 Lighting

Options

- Tow Sling or Medium Duty Tow Bar
- Scotch Blocks
- Snatch Blocks
- Chrome Decor Group
- Push Bumper
- Bolt-on-Boom Jib
- Extra Tool Boxes
- Light Bar
- Deluxe Switch Panel
- Work Lights
- Hook Up Lights
- Tool Box Lights
- Pintle Hitch with Ball
- Remote Control System