

# AATAC

AATAC's AMD Medium Duty Carrier offers several important advantages. First, the innovative and super tough "reverse hose track system" is designed for the least amount of wear and tear and the longest life of any other hose system available. The load capacity was designed with an outstanding 14,000-pound payload. The winch offers an extremely low clearance with a 10,000-pound capacity. A complete base frame reinforces the carrier unit and the truck chassis. All this and more makes the AATAC AMD the



toughest Medium Duty Carrier on the market Available in aluminum or steel, deck length of 19' - 22', and either solid or removable side rails.

# AMD

**AATAC Medium Duty Carrier**



## Standard Features

- 19" - 22" Steel or 19" Aluminum Body (AMD)
- 96" Wide Body
- Dual Front Lift Cylinders
- Extension Cylinder w/ Wear Rings
- Tubular Cab Protector
- Dual Illuminated Control Panels
- 6" Solid Sides
- Positive Lock Down System
- 12 Tie Down Plates (6 - Aluminum)
- Chassis Reinforcing Subframe
- 3/4 Length Lift Frame
- Full Length Nylatron Side Pads
- Reverse Hose Track System
- Variable Speed Hydraulic Winch
- 50í Cable
- Mud Flaps
- 36" x 14" x 16" Tool Box w/ key
- Tow Light Socket
- Safety Straps and Ratchets
- Sealed Wiring Connectors
- Factory Preassembled and Tested
- Complete Installation Hardware

## Options

- Cable Tensioner
- Remote Winch Freespool
- Extra Tool Boxes
- Aluminum Tool Box
- Door Covers
- Light Bar
- Deluxe Switch Panel
- Front Work Lights
- Hook Up Lights
- Tool Box Lights
- Side D-rings
- Removable Side Rails (Steel Only)
- 102" Wide Body (Steel Only)
- Tread Plate Floor (Steel Only)
- Trailer Hitch
- Pintle Hitch
- Various Cab Protector Styles
- Snatch Block
- V-Chains and Straps



19' AMD towing a Chevy Suburban



The low maintenance, easy to maintain, Reverse Hose Track System



Superior distance



## Specifications

Load capacity:	Steel.....	14,000 lbs
	Aluminum.....	10,000 lbs
Platform size:	Steel.....	19' - 22'
	Aluminum.....	18' 8" x 8'
Floor:	Steel.....	3/16" Solid Smooth Plate
	Aluminum.....	6061-T6 Air Craft Grade
Cross members.....	3" 58,000 PSI structural channel	
Tow bar capacity.....	3,500 Extended	
Wheel Lift capacity.....	3,500 Extended	
Winch.....	9,000 lbs, First Layer	
Cable.....	50' 3/8" 6 x 37	

Chassis recommended 14,250 to 24,000 GVW  
 Ratings are based on structural factors only, not vehicle capability.  
 Product specifications are subject to change without notice.

# AATAC

4000 Sam Wilson Rd Charlotte, NC 28214

1-800-228-0295

www.aatac.com

Distributed by:

