

TITAN 50



Elite Towing and Recovery

AATAC's Titan 50 series was developed with the towing operator in mind. The Titan 50 is designed for efficient weight transfer to maximize towing capabilities while providing superior strength and power to make the job easier. The integrated three-stage under-reach offers increased capacity and weight savings while providing an excellent reach and a 100% range of power tilt. The Titan 50 offers many features as standard that are options on other units, a few of which are: full function radio remote control, towing attachments, and LED Taillights. If you are looking for an elite heavy duty unit that is both versatile and affordable, then the Titan 50 is for you.

Standard Equipment

- 156" CA body
- Lumber Storage Box
- Modular Steel Body
- Deluxe Light Pylon
- Chain Racks & Tool Holders
- Illuminated Tool Compartments
- Pressure Gauges
- Dual Manual Controls
- Radio Remote Control
- Air Free Spools
- Air Cable Tensioners
- Hydraulic Jacks w/ Removable Pads
- Dual Hydraulic Pump
- LED Taillights
- Mud Flaps
- 1/2" x 15' Safety Chains
- 5/8" Hook Adapters
- Spring Lift Brackets
- Lo-Pro Fork Receivers
- Frame Forks, Risers & Adapters
- Sealed Wiring Harness
- Complete Installation Hardware
- Pre-Assembled and Factory Tested
- Federal Standard 108 Lighting

Optional Equipment

- Air Shift PTO
- Tandem Axle Toolboxes
- Air and Electrical Hookups
- Light Bar Packages and Switch Panels
- Work Light Sets
- Wide Load Tow Light Bar
- Aluminum Decor Kit
- Convenience Group
- Heavy Duty Truck Tire Lift
- Pintle Hook Attachments
- Fifth Wheel Plate
- Front Jacks w/ D-Rings
- Snatch Block (8" Sheave)



Power:	Retracted (TEMA)	50,000 lbs
	Extended (TEMA)	16,000 lbs
Boom Exte	ension	115"
Maximum	Boom Angle	40°
Maximum Boom Elevation		230"
Reach Past Underlift		98"

Underlift

Retracted Capacity	35,000 lbs
Extended Capacity at Third Stage	16,000 lbs
Extension Past Tailboard	113"
PositiveTilt	90°
Negative Tilt	8.5°

Winch

Planetary Winches (2 speed)	(2) 25,000 lbs each
Cable	5/8" x 200'

- *Chassis recommended tandem axle 33,000 minimum GVW
- *Ratings are based on structural factors only, not vehicle capability.
- *Product specifications are subject to change without notice.
- *Unit shown with Optional Equipment.

Distributed by:

AATAC 4000 Sam Wilson Road

Charlotte, NC 28214

1-800-228-0295