

AATAC

"Superior Quality, Strength and Durability"

TITAN 70



Superior by Design

AATAC's Titan 70 series is the elite in heavy duty towing and recovery. The Recovery boom incorporates style, simplicity, and function, designed to handle the toughest stresses without "breaking a sweat." The Titan 70 series also boasts the most advanced heavy duty under-reach system available. The integrated three-stage under-reach offers increased capacity and weight savings while providing a superior reach and 100% range of power tilt. The Titan 70 is loaded with standard features including, full function radio remote control, towing attachments, LED Taillights, and offers optional equipment such as front outriggers, allowing for greater stability and increasing recovery capability.

AATAC

TITAN 70

Standard Features

- 180" CT body
- Lumber Storage Box
- Modular Steel Body
- Deluxe Light Pylon
- Chain Racks & Tool Holders
- Illuminated Tool Compartments
- Pressure Gauges
- Dual Manual Controls
- Radio Remote Control
- Air Free Spools
- Air Cable Tensioners
- Hydraulic Jacks w/ Removable Pads
- Dual Hydraulic Pump
- LED Taillights
- Mud Flaps
- 1/2" x 15' Safety Chains
- 5/8" Hook Adapters
- Spring Lift Brackets
- Lo-Pro Fork Receivers
- Frame Forks, Risers & Adapters
- Sealed Wiring Harness
- Complete Installation Hardware
- Pre-Assembled and Factory Tested
- Federal Standard 108 Lighting

Options

- Air Shift PTO
- Air and Electrical Hookups
- Light Bar Packages and Switch Panels
- Work Light Sets
- Wide Load Tow Light Bar
- Aluminum Decor Kit
- Convenience Group
- Heavy Duty Truck Tire Lift
- Pintle Hook Attachments
- Fifth Wheel Plate
- Front Jacks w/ D-Rings
- Snatch Block (8" Sheave)

Recovery Boom

Power:	Retracted (TEMA).....	70,000 lbs
	Extended (TEMA).....	26,000 lbs
Boom Extension.....		130"
Maximum Boom Angle.....		40°
Maximum Boom Elevation.....		260"
Reach Past Underlift.....		116"

Underlift

Retracted Capacity.....	40,000 lbs
Extended Capacity at Third Stage.....	16,000 lbs
Extension Past Tailboard.....	135"
Positive Tilt.....	90°
Negative Tilt.....	8.5°

Winch

Planetary Winches (2 speed).....	(2) 35,000 lbs each
Cable.....	3/4" x 200'

*Chassis recommended tandem axle 50,000 minimum GVW

*Ratings are based on structural factors only, not vehicle capability.

*Product specifications are subject to change without notice.

*Unit shown with Optional Equipment

Distributed by:

AATAC
4000 Sam Wilson Road
Charlotte, NC 28214
1-800-228-0295

